

| CDX Tasksheet Number | TASKSHEET | ASC UK Vehicle Fitting & Roadside Assistance NVQ |
|----------------------|--|--|
| C106 | Diagnose clutch noise, binding, slippage, pulsation, and chatter; determine necessary action. | VF08 |
| C107 | Inspect clutch pedal linkage, cables, automatic adjuster mechanisms, brackets, bushings, pivots, and springs; perform necessary action. | VF08 |
| C108 | Inspect hydraulic clutch slave and master cylinders, lines, and hoses; determine necessary action. | VF08 |
| C109 | Inspect clutch release (throw-out) bearing, lever, and pivot; determine necessary action. | VF08 |
| C110 | Inspect and replace clutch pressure plate assembly and clutch disc. | VF08 |
| C111 | Bleed clutch hydraulic system. | VF08 |
| C112 | Inspect, remove or replace primary shaft pilot bearing or bushing (as applicable). | VF08 |
| C201 | Remove, inspect, and install suspension strut cartridge or assembly, strut coil spring, and insulators (silencers). | VF11 |
| C202 | Inspect, remove, and replace shock absorbers. | VF11 |
| C209 | Check and adjust front and rear wheel camber; perform necessary action. | VF07 |
| C210 | Check and adjust caster; perform necessary action. | VF07 |
| C211* | Check and adjust front wheel toe and center steering wheel; (adjust as needed). | VF07 |
| C212 | Center steering wheel. | VF07 |
| C213 | Check toe-out-on-turns (turning radius); determine necessary action. | VF07 |
| C214 | Check SAI (steering axis inclination) and included angle; determine necessary action. | VF07 |
| C215 | Check and adjust rear wheel toe. | VF07 |
| C216 | Check rear wheel thrust angle; determine necessary action. | VF07 |
| C219 | Diagnose tire wear patterns; determine necessary action. | VF01/2/3 |
| C220 | Inspect tires; check and adjust air pressure. | VF01/2/3 |
| C221 | Diagnose wheel/tire vibrations, shimmy, and noise; determine necessary action. | VF01/2/3 |
| C224 | Diagnose tire pull (lead) problem; determine necessary action. | VF01/2/3 |
| C225 | Balance wheel and tire assembly (static and dynamic). | VF01/2/3 |
| C226* | Dismount, inspect, (repair,) and remount tire on wheel. | VF01/2/3 |
| C227 | Reinstall wheel; torque lug nuts. | VF01/2/3 |
| C228 | Inspect and repair tire. | VF01/2/3 |
| C232 | Diagnose pressure concerns in the brake system using hydraulic principles (Pascal's Law). | VF12 |
| C233 | Measure brake pedal height; determine necessary action. | VF12 |
| C234 | Check master cylinder for internal and external leaks and proper operation; determine necessary action. | VF12 |
| C235 | Remove, bench bleed, and reinstall master cylinder. | VF12 |
| C236 | Diagnose poor stopping, pulling or dragging concerns caused by malfunctions in the hydraulic system; determine necessary action. | VF12 |
| C237 | Inspect brake lines, flexible hoses, and fittings for leaks, dents, kinks, rust, cracks, bulging or wear; tighten loose fittings and supports; determine necessary action. | VF12 |
| C238 | Fabricate and/or install brake lines (double flare and ISO types); replace hoses, fittings, and supports as needed. | VF12 |

| CDX Tasksheet Number | TASKSHEET | ASC UK Vehicle Fitting & Roadside Assistance NVO |
|----------------------|---|--|
| C239 | Select, handle, store, and fill brake fluids to proper level. | VF12 |
| C240 | Inspect, test, and/or replace brake system metering (hold-off), proportioning (balance), pressure differential, and combination valves. | VF12 |
| C241 | Inspect, test, and adjust height (load) sensing proportioning valve. | VF12 |
| C242 | Inspect, test, and/or replace components of brake warning light system. | VF12 |
| C243 | Bleed (manual, pressure, vacuum or surge) brake system. | VF12 |
| C244 | Flush hydraulic brake system. | VF12 |
| C245* | Diagnose poor stopping, noise, vibration, pulling, grabbing, dragging or pedal pulsation concerns in drum brakes; determine necessary action. | VF12 |
| C246 | Remove, clean (using proper safety procedures), inspect, and measure brake drums; determine necessary action. | VF12 |
| C247 | Refinish brake drum. | VF12 |
| C248 | Remove, clean, and inspect brake shoes, springs, pins, clips, levers, adjusters/self-adjusters, other related brake hardware, and backing support plates; lubricate and reassemble. | VF12 |
| C249 | Remove, inspect, and install drum brake wheel cylinders. | VF12 |
| C250 | Pre-adjust brake shoes and parking brake before installing brake drums or drum/hub assemblies and wheel bearings. | VF12 |
| C251 | Install wheel, torque lug nuts, and make final checks and adjustments. | VF12 |
| C252* | Diagnose poor stopping, noise, vibration, pulling, grabbing, dragging or pedal pulsation concerns in disc brakes; determine necessary action. | VF12 |
| C253 | Remove brake caliper assembly from mountings; clean and inspect for leaks and damage to caliper housing; determine necessary action. | VF12 |
| C254 | Clean and inspect brake caliper mounting and slides for wear and damage; determine necessary action. | VF12 |
| C255 | Remove, clean, and inspect disc brake pads and retaining hardware; determine necessary action. | VF12 |
| C256 | Disassemble and clean disc brake caliper assembly; inspect parts for wear, rust, scoring, and damage; replace seal, boot, and damaged or worn parts. | VF12 |
| C257 | Reassemble, lubricate, and reinstall brake caliper, pads, and related hardware; seat pads, and inspect for leaks. | VF12 |
| C258 | Clean, inspect, and measure disc brake rotor with a dial indicator and a micrometer; follow manufacturer's recommendations in determining need to machine or replace. | VF12 |
| C259 | Remove and reinstall disc brake rotor. | VF12 |
| C260 | Refinish disc brake rotor (according to manufacturer's recommendations). | VF12 |
| C261 | Adjust disc brake calipers equipped with an integrated parking brake system. | VF12 |
| C297 | Measure and diagnose the cause(s) of excessive key-off battery drain (parasitic draw); determine necessary action. | VF10 |
| C302 | Perform battery state-of-charge test; determine necessary action. | VF10 |
| C303 | Perform battery capacity test; confirm proper battery capacity for vehicle application; determine necessary action. | VF10 |
| C304 | Maintain or restore electronic memory functions. | VF10 |
| C305 | Inspect, clean, fill, and replace battery. | VF10 |
| C306 | Perform slow/fast battery charge. | VF10 |

| CDX Tasksheet Number | TASKSHEET | ASC UK Vehicle Fitting & Roadside Assistance NVQ |
|---------------------------------|---|---|
| C307 | Inspect and clean battery cables, connectors, clamps, and hold-downs; repair or replace as needed. | VF10 |
| C308 | Start a vehicle using jumper cables and a battery or auxiliary power supply. | VF10 |
| C428 | Inspect the integrity of the exhaust manifold, exhaust pipes, muffler(s), catalytic converter(s), resonator(s), tail pipe(s), and heat shield(s); perform necessary action. | VF09 |
| C523 | Carry out automotive industrial personal workplace requirements. | G2 |
| C533 | Store and use hazardous materials in the motor and related industries. | G2 |
| C539 | Associated Studies Tasksheet - Use of number - Solve problems using calculations with numbers expressed in different forms. | ICS |
| C587 | Perform battery capacity test(or conductance test) ; confirm proper battery capacity for vehicle application; determine necessary action. | VF10 |